IHALDRUP



The Haldrup C-60 is a powerfull and robust plot combine especially build to have the possibility to transport it on a trailer behind a car. Direct access to the conveyor, thresher and concave for quick cleaning.

TECHNICAL DETAILS

Engine options	Deutz Diesel, water cooled, 55 kW, 75 HP
Fuel tank	60
Transmission	2 speed hydrostatic – 0-20 km/h – electrohy- draulic
Tyres (front)	7.50 R16
Tyres (rear)	20x8.00-10
Speed	500 - 1700 r/min
Diameter	350 mm
Heeling width	640 mm
Thresher	Variable with variator
Concave	Wire distance 7 mm (with round bars) - 11 mm - 26mm
Sieves walker	Two-stage, 1.2m ²

Upper sieve	Lower sieve 22 mm – 1140 x 640 mm
Lower sieve	Louver sieve 15 mm – 1140 x 640 mm
Total sieves area	1.44 m ²
Cutting table	Width: 1250 - 1510 - 1740 mm Reel: 5 bars - speed and height adjustable Hydraulic knife
Maize header Gering- hoff	2 rows
Dimensions Length - Width - Height	from 5100 mm (without dividers) - from 1700 mm - from 1550 mm
Track width	from 1200 mm
External wheel	1500 mm
Weight	from 2500 kg



AGRICULTURAL PLANT HIRE



J 01733 840691

Poplar Farm, Coates Peterborough, PE7 2DU