IHALDRUP



The Haldrup C-85 is an universal and reliable plot combine giving satisfaction to its owner over the past 20 years. This combine has a high harvesting capacity and is able to work properly even under severe conditions, through its ruggedness.

TECHNICAL DETAILS

Engine	Deutz Diesel TCD 3.6 L4, water cooled 80 kW, 108 HP
Fuel tank	135
Tyres (front)	335/80 R18 or 405/70 R20 or 14.9 R24 TL 135 A8 X M27
Tyres (rear)	23x8.50-12 8PR or 11.0/65-12 8PR
Two-stage transmission	2 speed hydrostatic – 0-25 km/h – electrohy- draulic
Steering / Brakes	power / hydraulic fail safe
Thresher	Electrohydraulic varia- ble speed control
Diameter / Width	450 mm / 850 mm
Straw walkers	4 (3 in option) - 1.7 m ²
Concave (wire distance)	7 mm (with round bars) - 11 mm - 26 mm

Upper sieve	Louver sieve 22 mm – 1140 x 850 mm
Lower sieve	Louver sieve 15 mm – 1140 x 850 mm
Total sieves area	1.92 m ²
Weighing Mettler	3 pliable weighing cells
Cutting table	Width: 1250 - 1510 - 1740 - 2045 - 2350 - 3010 mm Reel: 5 bars - speed and height adjustable Hydraulic knife
Maize header Gering- hoff	2 rows
Dimensions Length - Width - Height	7600 mm - 2360 mm - 3100 mm (without cyclone)
Track width	1415 mm
External wheel	1755 mm
Special Options	NIRS, GPS



AGRICULTURAL PLANT HIRE

